


ARTICULO: 2293

Purgador Termostático y Eliminador de Aire

Thermostatic steam trap and Air Vent

Características	Features
1. Purgador Termostático y Eliminador de Aire. 2. Diseño Compacto. 3. Alta durabilidad y fácil mantenimiento. 4. Excelente eliminación de aire. 5. Filtro incorporado. 6. Extremos roscados según ISO 228/1. Condiciones de Trabajo: Máxima presión de Diseño del cuerpo: PN25. Presión máxima admisible (PMA): 23 bar. Temperatura máxima admisible (TMA): 235°C. Máxima presión diferencial: 21 bar. Instalación horizontal ó vertical.	1. Thermostatic steam trap and Air Vent. 2. Compact structure. 3. High durability and easy maintenance. 4. Excellent air discharge. 5. Built in Strainer. 6. Threaded ends according to ISO 228/1. Working Conditions: Body design conditions: PN25. Maximum allowable pressure (PMA): 23 bar. Maximum allowable temperature (TMA): 235°C. Maximum differential pressure: 21 bar. Horizontal or Vertical installation.



PARTES COMPONENTES – COMPONENT PARTS:

Nº	Nombre / Name	Material
1	Cuerpo / Body	Acero Inoxidable 304 / Stainless Steel 304
2	Malla Filtro / Strainer Screen	Acero Inoxidable 304 / Stainless Steel 304
3	Resorte / Spring	Acero Inoxidable / Stainless Steel (Inconel)
4	Purgador de Aire / Air Vent	Acero Inoxidable 304 / Stainless Steel 304
5	Base / Base	Acero Inoxidable 304 / Stainless Steel 304
6	Junta / Gasket	Acero Inoxidable 304 / Stainless Steel 304
7	Tapa / Cover	Acero Inoxidable 304 / Stainless Steel 304

DIMENSIONES – DIMENSIONS:

Ref.	Media / Size	Dimensiones / Dimensions		Peso / Weight (Kg)
		L	W	
2293 02	DN8	50	45	0,510
2293 03	DN10	58	45	0,510
2293 04	DN15	60	45	0,440

CAPACIDAD DE DESCARGA – DISCHARGE CAPACITY:

